

3.21 PRIMAFLEX KLIPP CAR-HT 300

Temperature range -60 °C to 300 °C



Description

Flexible lightweight clamping profile hose with a layer made of special coated hightemperature textile fabric and with galvanized steel clamping profile. Highly suitable for exhaust suction at higher temperatures.

Available in our online shop

Properties

- Superior temperature resistance
- Highly flame-retardant
- Good compressibility
- Flexible
- Small bending radii
- Vibration-resistant
- External clamping profile-scrubbing protection
- Mechanically highly resilient
- Abrasion resistant
- Tensile connection of wall and clamping profilel

Application ranges

Exhaust suction, Smoke suction

Length

Standard lengths: 2 - 10 m. According to specifications.

Further informations

Color: green-brown.

Clamping profile also in aluminum or VA (1.4512, 1.4301).

TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Length (m)	Article-No.
50	30	0,9	0,32	0,5	2 - 10	6155050
60	36	0,78	0,222	0,6	2 - 10	6155060
65	39	0,68	0,19	0,7	2 - 10	6155065
70	42	0,67	0,16	0,7	2 - 10	6155070
75	45	0,62	0,14	0,8	2 - 10	6155075
80	48	0,61	0,125	0,8	2 - 10	6155080
90	54	0,56	0,1	0,8	2 - 10	6155090
100	60	0,51	0,08	0,9	2 - 10	6155100
110	66	0,48	0,066	0,9	2 - 10	6155110
120	72	0,36	0,056	1	2 - 10	6155120
125	75	0,33	0,05	1	2 - 10	6155125
140	84	0,25	0,041	1,1	2 - 10	6155140
150	90	0,22	0,036	1,2	2 - 10	6155150
160	96	0,21	0,031	1,2	2 - 10	6155160
180	126	0,172	0,025	1,4	2 - 10	6155180
200	140	0,148	0,02	1,6	2 - 10	6155200
225	158	0,115	0,016	1,8	2 - 10	6155225
250	175	0,1	0,013	2	2 - 10	6155250
300	210	0,07	0,009	2,2	2 - 10	6155300
350	245	0,056	0,006	2,6	2 - 10	6155350
400	320	0,047	0,005	3,1	2 - 10	6155400
450	360	0,045	0,004	3,6	2 - 10	6155450
500	400	0,043	0,003	4,1	2 - 10	6155500
600	480	0,039	0,002	5,1	2 - 10	6155600
700	560	0,031	0,001	6	2 - 10	6155700
800	640	0,022	0,001	6,9	2 - 10	6155800
900	720	0,016	0,001	7,8	2 - 10	6155900