

2.09 PRIMAFLEX PVC GSS

Temperature range 0 °C bis 70 °C



Properties

- Flexible
- Lightweight to medium weight
- Smooth interior
- Wall thickness: 1,00 mm

Application ranges

Suction technology, Plant engineering, PVC hoses, Suction hoses, small shavings and solids

Length

Standard length: 10 m

Description

Medium weight pressure hoses, suction hoses, and transport hoses for universal applications.

Available in our online shop

TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Length (m)	Article-No.
30	45	2,2	0,8	0,405	10	6071030
40	60	2,1	0,6	0,54	10	6071040
50	75	1,9	0,4	0,68	10	6071050
60	90	1,6	0,35	0,7	10	6071060
70	105	1,3	0,3	0,865	10	6071070
75	110	1,2	0,3	0,94	10	6071075
80	120	1,2	0,3	0,94	10	6071080
100	150	1	0,25	1,34	10	6071100
125	185	0,75	0,2	1,6	10	6071125
150	225	0,5	0,18	2,06	10	6071150
175	260	0,35	0,16	2,28	10	6071175
200	300	0,3	0,15	2,76	10	6071200
250	375	0,2	0,12	3,73	10	6071250
300	450	0,15	0,1	4,74	10	6071300
350	525	0,1	0,09	5,22	10	6071350
400	600	0,1	0,08	6,3	10	6071400
450	675	0,08	0,06	6,71	10	6071450
500	750	0,050	0,040	7,480	10	6071500