

4.07 PRIMAFLEX SPIRA ISO L

Temperature range -40 °C bis 100 °C



Description

Insulated, flexible warm air hose, spiral hose. With insulation between the inner and outer layers of fabric. Outside with abatement protection. Handcrafted with special know-how quality product made of high-quality raw material.

Excellent for air-conditioning to mobile or stationary air-conditioning units, e.g. at airports to PCA systems. Also for energy-conscious air conditioning of halls, tents and buildings.

The insulation ensures low temperature loss.

Available in our online shop

Properties

- Insulated
- Lightweight
- Flexible
- High tensile strength
- Non-kinking
- Compressible
- With scuff protection
- Large diameters available
- Continuous connection possible
- Spiral-free sleeves

Application ranges

Hot air hoses, Air-conditioning and ventilation technology, Aircraft air-conditioning, external, Airport, PCA system

Length

Standard length: 7,6 m. Other lengths on request.

Further informations

Color: yellow-black.

Extras: end rings instead of end sleeves, Velcro closure for continuous installation.

TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Spiral spacing (mm)	Weight (kg/m)	Length (m)	Article-No.
203	150	1,06	according to customer requirements	Article-No. is assigned after specification
305	150	1,6	according to customer requirements	
356	150	1,87	according to customer requirements	
407	150	2,14	according to customer requirements	
457	150	2,4	according to customer requirements	
508	150	1,67	according to customer requirements	